


M2-M-18.5 DT



Dimensions

- Width x Height x Depth: 461 x 292 x 69 mm
- Weight: 7,5 kg ± 10%

Housing

- Chassis: Aluminium, RAL 9005 powder coated
- Cover electronics: Steel, RAL 9005 powder coated
- Front: Antireflex glass

Display

- 18.5" TFT Display
- Resolution: 1920 x 1080
- Brightness: 300 cd/m² (270 cd/m²)
- Contrast ratio: 5000:1
- Full range dimming: 0-100 %
- With or without PCAP Multi-Touch

Video Input		2 x DVI Input 1 x VGA Input
M2 Controller Board	Feature	1 x RS232, RS485/422 (configurable) 1 x Internal Alarm Buzzer 1 x Touch USB 1 x BUZZER OUTPUT 1 x EXT LED (2 LEDs) 1 x EXT BKLT CTRL (2 Buttons UP/DOWN, 1 Potentiometer) 1 x SOURCE SELECT (Video Input)
Power Options	DC	24 VDC
	AC	230/115 VAC (50/60Hz)
	DCAC	24 VDC, 230/115 VAC (50/60Hz)
	Power Rating	30 VA
Environment	Operating Temp.	-15 to +55 °C
	Storage Temp.	-20 to +70 °C
	IP Rating	IP66 (front) - IP20 (rear)
Compass Safe Distance	Standard Compass	0.85 m in all directions
	Steering Compass	0.65 m in all directions
Type Approval		DNV, Tested according to EN 60945 EU-RO-MR ^(*)


^(*) expected Q1/2023

Options and additional features are configurable. Contact your Sonove sales representative for further information. Depending on the product configuration, interfaces or slot brackets may differ from the figures in this document.

M2-M-18.5 DT



Drawings



Sonove GmbH
Hindelanger Str. 33
87527 Sonthofen
Deutschland

Tel. +49 8321 67466 200
Fax +49 8321 67466 199
marine@sonove.com