

# M2-PPC-24HB DT (S)

## 6th Generation Intel® Core™ Processors



### Dimensions

- Width x Height x Depth: 574 x 341 x 75 mm
- Weight: 11 kg ± 10%

### Housing

- Chassis: Aluminium, RAL 9005 powder coated
- Cover electronics: Steel, RAL 9005 powder coated
- Front: Glass, antireflex coated both sides

### Display

- 24" TFT High Bright Display
- LED Backlight
- Resolution: 1920 x 1080
- Brightness: 1000 cd/m<sup>2</sup>
- Full range dimming: 0-100 %
- With or without PCAP Multi-Touch

<b>System</b>	Processor	6th Generation Intel® Core™ Processors Intel® Core™ i7-6600U, 2 Cores, 4M Cache, 2.60 GHz up to 3.40 GHz Intel® Core™ i5-6300U, 2 Cores, 3M Cache, 2.40 GHz up to 3.00 GHz	
	Memory	Up to 16GB, Dual Channel DDR3L 1600MHz	
	Storage	1 x mSATA SSD up to 1TB 2 x SSD up to 2TB RAID 0/1/5	
<b>Graphics</b>	Controller	Intel® HD Graphics 520	
	Feature	OpenGL 4.4, DirectX 12, OpenCL 2.1 HW Decode: AVC/H.264, MPEG2, VC1/WMV9, JPEG/MJPEG, HEVC/H265, VP8, VP9 HW Encode: AVC/H.264, MPEG2, JPEG, HEVC/H265, VP8, VP9	
	Dual Displays	1 x DP + 1 x DP++	
<b>Expansion</b>	Interface	1 x PCIe x4 (Gen3) Low Profile	
<b>Rear I/O</b>	Ethernet	2 x GbE (RJ-45)	Optional up to 4 x GbE
	USB	4 x USB 3.0	Optional up to 8 x USB
	Display	1 x DP 1 x DP++	
	Audio	1 x Line-out 1 x Mic-in	
	Serial		Optional up to 4 x COM (RS232 or 422/485)
<b>Optional (M2 CB)</b>	Controller	M2 Controller Board	
	Feature	1 x Internal Alarm-Buzzer 1 x Out for ext. Alarm-Buzzer 1 x Potentiometer In, 2 x Push Button In 2 x Out for Status LED	
<b>Watchdog Timer</b>	Output & Interval	System Reset, Programmable via Software from 1 to 255 Seconds	
<b>Security</b>	TPM	dTPM 2.0 (available upon request)	
<b>Power Options</b>	DC	24 VDC	
	AC	230/115 VAC (50/60Hz)	
	DCAC	24 VDC, 230/115 VAC (50/60Hz)	
<b>OS Support</b>	Microsoft/ Linux	Windows 7 64-bit Windows 8.1 64-bit Windows 10 IoT Enterprise 64-bit Linux	
<b>Environment</b>	Operating Temp.	-15 to +55°C	
	Storage Temp.	-20 to +70°C	
	IP Rating	IP66 (front) - IP20 (rear)	
<b>Compass Safe Distance</b>	Standard Compass	1.10 m in all directions	
	Steering Compass	0.75 m in all directions	
<b>Type Approval</b>		DNV GL	
		Tested according to EN 60945	
		DNV, Tested according to EN 60945 EU-RO-MR(*)	

(\*) expected Q1/2023


Options and additional features are configurable. Contact your Sonove sales representative for further information.  
Depending on the product configuration, interfaces or slot brackets may differ from the figures in this document.

# M2-PPC-24HB DT (S)

6th Generation Intel® Core™ Processors



## Drawings



Sonove GmbH  
Hindelanger Str. 33  
87527 Sonthofen  
Deutschland

Tel. +49 8321 67466 200  
Fax +49 8321 67466 199  
marine@sonove.com